

MATERIAL SAFETY DATA SHEET

DBP DLC®-A


Date Revised: June 20, 2000

Page 1 of 4

SECTION I - PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME: DBP DLC-A

CHEMICAL NAME: Dibutyl Phthalate on Silicon Dioxide

Company:  NATROCHEM, INC.
P.O. Box 1205
Savannah, GA 31402-1205

HMIS RATING	
Health	1
Flammability	1
Reactivity	0

Telephone Numbers:

Transportation Emergencies:

CHEMTREC (U.S.A.): (800) 424-9300 (24 hours)

CHEMTREC (International): (202) 483-7616 (24 hours, call collect)

Product Information:

SECTION II - HAZARDOUS INGREDIENTS

The component(s) listed below is identified as a hazardous chemical under the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

INGREDIENT	CAS #	ACGIH (TLV)	OSHA (PEL)	UNITS
Dibutyl Phthalate	84-74-2	5	5	mg/m ³
Silicon Dioxide	7631-86-9	10	6	mg/m ³

SECTION III - PHYSICAL DATA

Boiling Point: 644° F

Specific Gravity: 1.206

Vapor Pressure (mm Hg): 1 @ 20° C

Percent Volatiles: N/DA

Vapor Density (Air = 1): 9.6

Evaporation Rate: Negligible

Solubility in Water: Negligible

Appearance and Odor: Off-white, free-flowing powder with no odor.

SECTION IV - FIRE & EXPLOSION DATA

FLASH POINT (Method Used): 375° F (COC)

FLAMMABLE LIMITS: LEL- 0.47 @ 457° F, UEL- N/D

AUTOIGNITION TEMPERATURE: 759° F (ASTM D2155)

EXTINGUISHING MEDIA: Water spray, dry chemical, CO₂, foam.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE & EXPLOSION HAZARDS: None known.

SECTION V - HEALTH HAZARD DATA

CHRONIC HEALTH EFFECTS: An epidemiological study was conducted which included 165 precipitated silica workers who had been exposed for an average of 18 years. No adverse effects were noted in complete medical examination (including chest roentgenograms) of these workers. Pulmonary function decrements were correlated only with smoking and age but not with the degree or duration of dust exposure. Laboratory studies have also been conducted in small animals via inhalation to levels of precipitated silica dust of up to 126 mg/m³ for periods from six months to two years. Although precipitated silica was temporarily deposited in the animal's lungs, most of the deposited material was cleared soon after the dust exposure ended. The results of all studies performed by, or known to, PPG indicate a very low order of pulmonary activity for synthetic precipitated silica.

SECTION V - HEALTH HAZARD DATA (cont)

CHRONIC: High oral doses of this material given to pregnant animals produced some minor abnormalities in their offspring. However, high doses to humans handling this material are not expected since oral consumption is not a likely route of significant exposure. Because this material does not evaporate readily and is not easily absorbed through the skin, it is not expected to produce such effects in humans through inhalation or skin exposure when handled in a manner consistent with the precautionary measures contained in this material safety data sheet.

PRIMARY ROUTE OF ENTRY- Inhalation, skin contact, eye contact.

CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN: None

NTP: No

IARC: No

OSHA: No

EFFECTS OF EXPOSURE-

EYES- Mildly irritating. Excessive contact with powder can cause drying of mucous membranes of eyes due to absorption of moisture and oils.

SKIN- Mildly irritating.

INHALATION- Nuisance dust. Excessive contact with powder can cause drying of mucous membranes of nose and throat due to absorption of moisture and oils. This material can also cause nasal irritation and nosebleeds.

INGESTION- Not significantly toxic.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE- Persons with breathing problems or lung disease should not work in dusty areas unless a physician approves and certifies their fitness to wear respiratory protection.

SECTION VI - EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: Immediately rinse with clean water for 15 minutes. Retract eyelids often. If irritation persists, seek medical attention.

SKIN CONTACT: Immediately remove contaminated clothing. Wash skin thoroughly with mild soap and water. Flush with lukewarm water for 15 minutes. Seek medical attention if ill effect or irritation develops.

INHALATION: If overcome by exposure, remove victim to fresh air. If symptoms persist, consult a physician.

INGESTION: Consult a physician.

SECTION VII - REACTIVITY DATA

STABILITY: Stable.

MATERIALS TO AVOID- Avoid alteration of product properties before reuse. Calcining, which may result in crystalline formation or mixing with additives may alter toxicological properties. Strong oxidizing agents.

SECTION VII - REACTIVITY DATA

CONDITIONS TO AVOID- Avoid high temperatures (> 800° C) treatment.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon when burned.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VIII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: MINIMIZE SPILL AREA. Vacuum spill material and place in closed plastic bags for disposal. Prevent runoff from entering sewers, drains, or streams.

WASTE DISPOSAL METHOD: In accordance with local, state, and federal regulations.

SECTION IX - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use a respirator such as 3M 9900 or equivalent for protection against pneumoconiosis producing dusts.

VENTILATION: Provide explosion proof ventilation as required to control airborne dust levels. The sum total of all ingredients may emit vapors during normal processing. All possible health effects are not known and individual sensitivities will vary. Effective exhaust ventilation should always be provided to draw dust, fumes and vapors away from workers to prevent routine inhalation. Ventilation should be adequate to maintain ambient workplace atmosphere below the limits listed in Section V.

PROTECTIVE GLOVES: Impervious gloves to protect against contact with product.

EYE PROTECTION: Safety goggles.

OTHER PROTECTIVE EQUIPMENT: Protective clothing, eye wash station, safety shower.

SECTION X - SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Handling can create explosive dust clouds. Eliminate ignition sources, use explosive proof equipment. Conveying and processing equipment should be spark-proof, well bonded and grounded. Avoid dust accumulations. Keep from contact with oxidizing materials. Keep container closed.

OTHER PRECAUTIONS: Wash with soap and water before eating, drinking, smoking, or using toilet facilities. Launder contaminated clothing before reuse.

SECTION XI - REGULATORY INFORMATION

TOXIC SUBSTANCE CONTROL ACT (TSCA):

The components of this product are contained on the Inventory of the Toxic Substance Control Act.

SARA TITLE III INFORMATION:

SECTION 313 - TOXIC CHEMICALS:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372):

CAS REGISTRY #	CHEMICAL NAME	PERCENT BY WEIGHT
84-74-2	Dibutyl Phthalate	72

This information must be included in all MSDS' that are copied and distributed for this material.

RCRA STATUS:

The following components are listed under (40 CFR 261):

Dibutyl Phthalate (Ref. 261.33(f))

SECTION XI - REGULATORY INFORMATION (Cont.)

SECTION 302 - EXTREMELY HAZARDOUS SUBSTANCES:

This product does not contain an extremely hazardous substance.

SECTION 311/312 - HAZARD CATEGORIES:

The physical and health hazard categories for this product are:

Fire Hazard: None

Sudden Release of Pressure Hazard: None

Reactivity Hazard: None

Immediate (Acute) Health Hazard: Silicon Dioxide

Delayed (Chronic) Health Hazard: None

TRANSPORTATION INFORMATION:

DOT Shipping Name: RQ (10 lbs.), Environmentally hazardous substance, 9, UN3077, III, Marine Pollutant

DOT Identification Number: N/DA

SECTION XII - OTHER INFORMATION

Revision Note: Added CHEMTREC information.

Prepared by: James L. Pye, Jr.

Title: Safety Coordinator

N/A = Not applicable N/D = Not determined N/DA = No Data Available

N/E = Not established

The information given in this MSDS was obtained from sources which we believe are reliable. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse are beyond our control, Natrochem, Inc. makes no warranty express or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon.