



NATROCHEM INC.
P.O. BOX 1205
SAVANNAH, GA 31402
(912) 236-4464 FAX: (912) 236-1919
www.natrochem.com

DATA SHEET LP32C DLC®-A

LP32C DLC-A is a liquid polysulfide polymer, silicon-dioxide blend. Its' widest application is in the building industry. Product is a free-flowing powder that exhibits excellent adhesion to many different surfaces and materials, outstanding resistance to salt and fresh water, weathering oxidation, ozone and high and low temp environmental conditions.

TEST	TEST METHOD	SPECIFICATION
Actives Content, %	QCL-8.2.4-2-1	70 - 74
Carrier Content, %	QCL-8.2.4-2-1	26 - 30

TYPICAL PROPERTIES

Actives Content, %	72.0
Carrier Content, %	28.0
Specific Gravity (Apparent)	1.41
Packaging	50# Net, Multi-Wall Bags
Color	Off-White

Date: 11/29/04

The information in this data sheet is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of these data or the use of this product, nor are any statements in this bulletin intended as recommendations to use our products in the infringement of any patents.

OTHER NATROCHEM PRODUCTS

**DLC® - Galex® - Rosin Oils - Rosin Pitches - Tarene™
Natro-Flex™ - Tar-Cel® - Natro-Cel®**