



**NATROCHEM, INC.**  
P.O. BOX 1205  
SAVANNAH, GA 31402  
(912) 236-4464 FAX: (912) 236-1919  
[www.natrochem.com](http://www.natrochem.com)

## **DATA SHEET**

### **NATRO-CEL® TACK 10-A**

Natro-Cel Tack 10-A is a plasticizer/tackifier, silicon-dioxide blend. It is used in pressure sensitive hot melts, and sealants. It enhances tack, lowers melt viscosity, and improves flexibility and low temperature properties.

<b>TEST</b>	<b>TEST METHOD</b>	<b>SPECIFICATION</b>
Actives Content, %	QCL-8.2.4-2-1	70 - 74
Carrier Content, %	QCL-8.2.4-2-1	26 - 30

#### **TYPICAL PROPERTIES**

Actives Content, %		72
Carrier Content, %		28
Specific Gravity (Apparent)		1.08
Packaging	40# Net, Multi-wall Bags	
Color		Off-White

Date of Revision: 08/22/03

The information in this data sheet is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of these data or the use of this product, nor are any statements in this bulletin intended as recommendations to use our products in the infringement of any patents.

#### **OTHER NATROCHEM PRODUCTS**

**DLC® - Galex® - Rosin Oils - Rosin Pitches - Tarene™**  
**Natro-Flex™ - Tar-Cel® - Natro-Cel®**