



NATROCHEM, INC.
P.O. BOX 1205
SAVANNAH, GA 31402
(912) 236-4464 FAX: (912) 236-1919
www.natrochem.com

DATA SHEET VULKANOL OT DLC-A

Vulkanol OT DLC-A is an ether thioether, silicon-dioxide blend synthetic plasticizer for NR's and SR's. It has good compatibility with the various polymers, e.g. NR, SBR, NBR, and CR, and it gives the vulcanizates excellent low-temperature flexibility. Because of its low volatility, it gives a very good compromise between low-temperature flexibility and good hot air resistance. Compared with many other plasticizers, Vulkanol OT DLC-A gives good adhesion to metals of molded and extruded rubber articles.

TEST	TEST METHOD	SPECIFICATION
Actives Content, %	QCL-8.2.4-2-1	70 - 74
Carrier Content, %	QCL-8.2.4-2-1	26 - 30

TYPICAL PROPERTIES

Actives Content, %		72
Carrier Content, %		28
Specific Gravity (Apparent)		1.13
Packaging	50# Net, Multi-wall Bags	
Color		Off-White

Date of Revision: 08/20/03

The information in this data sheet is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of these data or the use of this product, nor are any statements in this bulletin intended as recommendations to use our products in the infringement of any patents.

OTHER NATROCHEM PRODUCTS

**DLC[®] - Galex[®] - Rosin Oils - Rosin Pitches - Tarene[™]
Natro-Flex[™] - Tar-Cel[®] - Natro-Cel[®]**